




KTH AD-3 SLIDING DOOR





FEATURES

- "PFC" Device (Power Factor Correction).
- Catch-return Safety System: During the door motion if there is a person or object block the travel line, the door will return.
- A wide range of AC Voltage Input (AC100~AC240V).
- No restrictions for used places, the best choice for city architectures. With top security device, no misgivings about danger.
- Excellent Quality & High-performance.
- Safety Certificate: CE
Factory Certificate: URS ISO 9001
En16005: The latest regulation for the safety functions of automatic door in Europe.



NOISELESS



TYPE	AD-3	
MODEL	SINGLE-WINGED	BI-PARTING
DOOR WEIGHT	150kg X1(DOOR)	130kg X2(DOOR)
DDOOR WIDTH	500mm~2500mm	500mm~2500mm
INSTALL WAY	SURFACE INSTALL	SURFACE INSTALL
MOTOR	DC24V 75W WORM GEAR MOTOR	
CONTROL	USER-FRIENDLY MICRO-CONTROL	
POWER CONSUMPTION	75W	
VOLTAGE	AC100V~240V	
ENVIRONMENTAL TEMPERATURE	-20℃~+50℃	
VOLUME	60 DECIBEL(MAX.)	
STARTING SPEED	600mm/SEC.	550mm/SEC.
STARTING TIME	0~64 SEC. (REGULABLE)	
TRANSMISSION IMPORTANT CONDITION	RACK BELT S8M	
OPENING DOOR RANGE	FULL/HALF-OPEN (REGULABLE)	
PFC POWER EFFICIENCY	0.95(IN AC100V FULL LOAD)	
TRACTION FORCE	3.5 kg	