

H-10 Heavy Duty Door (Single / Bi-parting)

- It can provide protection for factories, hospitals, military bases and other areas that require high security.
- It can choose to install sensor or infrared protective device.
- Use wear resistant large wheels to decrease volume and extend service lifetime
- Use high-quality belt, which have small stretchability, are not affected by temperature, and have high transmission efficiency.

H - 10 Specification

MODEL	SINGLE-WINGED	BI-PARTING
DOOR WEIGHT	700kg X1/ (D00R)	500kg X2/(D00R)
DOOR WIDTH	DW=0.5M~6M	DW=0.5M~12M
INSTALL WAY	SURFACE INSTALL	SURFACE INSTALL
MOTOR	DC24V 120W BRUSHLESS DC MOTOR	
CONTROL	USER-FRIENDLY MICRO-CONTROLLER	
VOLTAGE	either AC100V~240V	
ENVIRONMENTAL TEMPERATURE	-20℃~+50℃	
VOLUME	60decibel (max.)	
STARTING SPEED	600mm/ (second)	550/ (second)
STARTING TIMES	0~20 sec. (regulable)	
TRANSMISSION IMPORTANT CONDITION	S8M RACKBELT	
OPENING DOOR RANGE	FULL/HALF-OPEN (regulable)	
PFC POWER EFFICIENCY	0.95	
TRACTION FORCE	WHEN POWER OFF THE DOOR CAN BE OPENED BY MANUAL	

